

HTMTM
SENSORS

HAND PROTECTION
30 mm / 1/18 in. RESOLUTION



- CATEGORY 4 SAFETY LIGHT CURTAINS
- RUGGED C-CHANNEL ALUMINUM HOUSING WITH ROTATING BRACKETS
- AVAILABLE FROM 6" TO 70" PROTECTIVE HEIGHT
- FAST RESPONSE TIMES, AND LONG 19 m OPERATING DISTANCE
- AVAILABLE WITH MIRRORS, AND IP69 ENCLOSURES
- DIGITAL DISPLAY FOR DIAGNOSTICS AND EASY ALIGNMENT

SAFETY LIGHT CURTAINS - CATEGORY 4 HAND PROTECTION SPECIFICATIONS



CV-A1-20-B03 / B10



CSME-03VU24-Y14



CABLES (3 m / 10 m)

RELAY

HSC4-30



LIGHT CURTAINS

MODEL	BEAMS	RESPONSE TIME	PROTECTIVE HEIGHT	TOTAL HEIGHT
HSC4-30-06	8	9 ms	150 mm (5.91 in.)	233.3 mm
HSC4-30-12	16	11 ms	300 mm (11.81 in.)	383.2 mm
HSC4-30-18	24	13 ms	450 mm (17.72 in.)	533.2 mm
HSC4-30-24	32	15 ms	600 mm (23.62 in.)	683.2 mm
HSC4-30-30	40	16 ms	750 mm (29.53 in.)	833.2 mm
HSC4-30-36	48	18 ms	900 mm (35.43 in.)	983.2 mm
HSC4-30-42	56	19 ms	1050 mm (41.34 in.)	1133.2 mm
HSC4-30-48	64	21 ms	1200 mm (47.24 in.)	1283.3 mm
HSC4-30-54	72	23 ms	1350 mm (53.15 in.)	1433.2 mm
HSC4-30-60	80	25 ms	1500 mm (59.06 in.)	1583.3 mm
HSC4-30-65	88	26 ms	1650 mm (64.96 in.)	1733.3 mm
HSC4-30-70	96	28 ms	1800 mm (70.87 in.)	1883.3 mm

NOTE: Specifications subject to change without notification.

CATEGORY 4 SAFETY LIGHT CURTAINS ARE IDEAL FOR PROTECTING PEOPLE FROM DANGEROUS MACHINERY WHERE HARD GUARDS ARE NOT PRACTICAL.

