


HTMTM
SENSORS



- STANDARD RANGE SENSORS FOR THE DETECTION OF METAL TARGETS
- LOWEST PRICE OF ALL THE MAJOR BRANDS FOR STANDARD SENSORS
- 1,000'S IN STOCK FOR SAME DAY DELIVERY
- STANDARD LIFETIME WARRANTY AGAINST DEFECTS
- RELIABLE NON-CONTACT OPERATION FOR MANY TYPES OF MACHINES
- IDEAL FOR USE WHERE A LOW-COST SENSOR IS NEEDED FOR DETECTION



STANDARD RANGE PROXIMITY SENSORS SPECIFICATIONS



SENSING DISTANCE	1 mm	1 mm	2 mm	5 mm	10 mm
OPERATING VOLTAGE	10-30 VDC				
OPERATING TEMPERATURE	-25 °C - +70 °C				
MOUNTING STYLE	Shielded				
HOUSING MATERIAL	Stainless Steel	Chrome Plated Brass			
PART NUMBERS					
DC 3-wire 10-30 V PNP - Open	FCU1-0801P-ACU3	FCM1-0801P-ARU4	FCM1-1202P-ARU4	FCM1-1805P-ARU4	FCM1-3010P-ARU4
DC 3-wire 10-30 V PNP - Closed	FCU1-0801P-BCU3	FCM1-0801P-BRU4	FCM1-1202P-BRU4	FCM1-1805P-BRU4	FCM1-3010P-BRU4
DC 3-wire 10-30 V NPN - Open	FCU1-0801N-ACU3	FCM1-0801N-ARU4	FCM1-1202N-ARU4	FCM1-1805N-ARU4	FCM1-3010N-ARU4
DC 3-wire 10-30 V NPN - Closed	FCU1-0801N-BCU3	FCM1-0801N-BRU4	FCM1-1202N-BRU4	FCM1-1805N-BRU4	FCM1-3010N-BRU4
DC 2-wire 10-60 V - Open	FCU1-0801C-ACU3	FCM1-0801C-ARU4	FCM1-1202C-ARU4	FCM1-1805C-ARU4	FCM1-3010C-ARU4
DC 2-wire 10-60 V - Closed	FCU1-0801C-BCU3	FCM1-0801C-BRU4	FCM1-1202C-BRU4	FCM1-1805C-BRU4	FCM1-3010C-BRU4

Short body versions available upon request.

NOTE: Specifications subject to change without notification.

STANDARD RANGE SENSORS HAVE THE BEST PRICE
OF ALL THE MAJOR BRANDS FOR APPLICATIONS THAT
REQUIRE A RELIABLE AND LOW-COST SENSOR.

